



WPR-8 ET2

Professional washers



VERSATILITY

STANDARD <> SELF-SERVICE

ELECTRIC <> HOT WATER

VALVE <> DRAIN PUMP

SINGLE <> STACKED

Suitable for many sectors: gyms, restaurants, campings, laundromats...



FEATURES

FEATURES

High G Factor 450.

ET2 control with a 4,3" touch screen easy to use and fully programmable

8 dosing signals as standard

USB connection. Free software online for programming, telemetry, data analysis...

WET CLEANING as standard

Short washing cycles (heating power 6 kw)



CONNECTIVITY

Danube Online communication - IoT as standard

Remote maintenance

Management of laundry

Multi-payment system



EFFICIENCY

Optimized consumption: automatic or manual adjustment of water levels and detergents according to the load
High G factor: reduced residual moisture, reduced drying time, energy savings
Water Saving system: 3 configurable levels of savings



ROBUSTNESS

Skinplate outer casing, aluminium door

AISI-304 stainless steel drum, vat and ribs

No inner drum seal: easy to clean

Industrial house bearing and bearings: until

20 000 working hours

Industrial gear and inverter

Industrial door locking system



OTHERS

Free standing: no anchoring to the floor

2 water inlets

4 compartments detergents box

Leveling feet included

Models with drain valve or with drain pump

Imbalance controlled by frequency inverter

CE and WRAS certificates




OPTIONS

- Dosing pumps kit DQ-2
- Additional dosing pump DB-1
- DD double drain kit WPR 8-10 (only model with valve)
- P Drain to pump transformation kit WPR-8/10
- Transformation kit pump to valve WPR-8/10
- SG door silicon gasket WPR 8-10
- RD reverse door opening
- TR Tropicalized model (ET2)
- DS Upper detergent box for WPR 8-10
- XD 6 extra dosing signals card WPR 8-10
- NC Normally closed valve
- Ergonomic plinth WPR-DPR - skinplate
- Ergonomic plinth WPR-DPR - stainless steel
- Mops plinth WPR 8-10 - skinplate
- Mops plinth WPR 8-10 - stainless steel
- Water recovery plinth WPR 8-10 - skinplate
- Water recovery plinth WPR 8-10 - stainless steel
- SSC AISI-304 Stainless steel outer casing WPR 8-10
- UD Kit temporized door opening WPR 8-10
- Supl 380-440V III 50/60 Marine WPR 8-10
- Supl 110-120V/50-60 Hz WPR 8-10
- Several payment systems for self-service
- IoT licence - Danube Online

DRUM	UNIT.	WPR-8 ET2	
Capacity 1/9	Kg	9	
Capacity 1/10	Kg	8	
Volume	l	80	
Diameter	mm	532	
Depth	mm	360	
GENERAL DETAILS			
Washing speed / Spining speed	r.p.m.	50 / 1250	
G Factor	-	450	
Maximum force transmitted	KN	1,47±0,53	
Frequency-dynamic force	Hz	18,33	
Noise level	dB	<70	
Coin laundry version	-	YES	
Double drain	-	OPT.	
Weighing system / Tilting door	-	NO	
SLUICE option	-	NO	
DOOR			
Height center door / Height door	mm	537 / 280	
Diameter	mm	373	
POWER			
Motor	kW	0,75	
Electric heating power	kW	6	
Total electric power (electric model)	kW	6,25	
Total electric power (hw, steam model)	kW	0,75	
CONNECTIONS		E	HW
Tension 110V - I + N + T	Nº x mm² / A	-	2x1,5+T - 16A
Tension 230V - I + N + T	Nº x mm² / A	2x6+T - 40A	2x1,5+T - 16A
Tension 230V - III + T	Nº x mm² / A	3x2,5+T - 20A	-
Tension 400V - III + N + T	Nº x mm² / A	4x1,5+T - 16A	-
Steam inlet (Steam model)	inch	NO	
Maximum steam consumption (Steam model)	Kg/h	-	
Water inlet	inch	3/4"	
Water main pressuer	Kgs/cm²	2-4	
Drain valve	mm/inch	2"	
Drain pump	mm/inch	1"	
Drainage capacity	Lit/min	140	
DIMENSIONS / PACKING DIMENSIONS			
Net / Gross width	mm	680 / 710	
Net /Gross depth	mm	698 / 832	
Net / Gross height	mm	1.040 / 1.158	
Net / Gross weight	Kg	150 / 161	
Volume	m³	0,49 / 0,68	





1. Soap dispenser
2. USB port
3. Drain valve/pump
4. Main switch
5. Liquid soap connection
6. Electrical connection
7. Liquid soap inlet
8. Cold water inlet
9. Hot water inlet
10. Ethernet port

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
WPR-8 V/P	680	698	1 040	278	373	86	964	962	922	942	954	110	366	427	524	603	199
WPR-10 V/P	680	742	1 040	278	373	86	964	962	922	942	954	110	366	427	524	603	199